

Benefits

1. optimum engine cleanliness leads to reduced CO2 emissions
2. stable lubricating film under aggravated operating conditions
3. suitable for LPG / CNG engines

Product Description

BIZOL Allround 10W-40 is a high-performance, low friction engine oil manufactured using the latest additive technology and synthetic components. It is suitable for all year-round use in passenger cars with gasoline and diesel engines with or without turbochargers and charge-air coolers. Also suitable for LPG/CNG engines according to the manufacturer's instructions.



Base Oil

HC-Synthetic

Specifications/Approvals & Recommendations

ACEA A3/B3 | API SN/CF | JASO MA

MB 229.1 | VW 501 01/505 00 | Renault RN 0700 | Peugeot B71 2294 |

Fiat 9.55535 G2

Available Packages

1 L Art. 83010 4 L Art. 83016 5 L Art. 83011 20 L Art. 83012

60 L Art. 83013 200 L Art. 83014

Technical Data

Name	Value	Method
Viscosity class SAE	10W-40	
Viscosity at 40 °C	88,5 mm ² /s	ASTM D 7042
Viscosity at 100 °C	13,3 mm ² /s	ASTM D 7042
Viscosity index	151	ASTM D 2270
Density at 15 °C	870 kg/m ³	DIN EN ISO 12 185
Pour Point	-36 °C	ISO 3016

Technical Data

Name	Value	Method
Flash Point (Cleveland)	220 °C	ISO 2592
ASTM colour number	L3,5	ASTM D1500
Evaporation loss	9,2 %	DIN 51 581
Total base number (TBN)	9,0 mg KOH/g	ASTM D 2896

Instructions

On refilling and changing the Engine Oil please follow the operating instructions of the manufacturer.