

## Benefits

1. optimum friction characteristics ensure reliable operation
2. outstanding fluidity at low temperatures
3. excellent high temperature protection

## Product Description

BIZOL ATF DIII+ is an universal automatic transmission oil. This oil is used in automatic gearboxes of passenger cars, trucks, buses and special vehicles as well as in hydraulic converters, hydraulic power steering systems and hydraulic clutches. High-quality base oil and selected additives in BIZOL ATF DIII+ ensure excellent driving properties even under heavy loads. Particularly worth mentioning is the good compatibility with various sealing materials.



## Base Oil

HC-Synthetic

## Specifications/Approvals & Recommendations

GM Dexron III H

Ford Mercon/ESP-M2C 166 H/ESP-M2C 138 CJ | MB 236.2 | Allison C4 |

Caterpillar TO-2

## Available Packages

1 L Art. 22850

5 L Art. 22851

20 L Art. 22852

## Technical Data

Name	Value	Method
Viscosity at 40 °C	36,5 mm <sup>2</sup> /s	ASTM D 7042
Viscosity at 100 °C	7,4 mm <sup>2</sup> /s	ASTM D 7042
Viscosity index	174	ASTM D 2270
Density at 15 °C	860 kg/m <sup>3</sup>	DIN EN ISO 12 185
Pour Point	<-51 °C	ISO 3016
ASTM colour number	> L8,0 (red)	ASTM D1500

## Technical Data

Name	Value	Method
Flash Point (Cleveland)	200 °C	ISO 2592

## Instructions

On refilling and changing the motor/gear oil please follow the operating instructions of the manufacturer.