

## Product Description

EP lubricants with outstanding lubricating and wear protection properties. Produced from high-quality base oils and the most modern sulphur-phosphorus additives. Suitable for use in industrial gears, roller and plain bearings with high pressure loads and especially in large plants with circular lubrication.

## Specifications/Approvals & Recommendations

DIN 51 517 Part 3/CLP | ISO 12925-1 - CKC ; CKD | AGMA 9005-E02 | AISE 224 | David Brown S1.53.101 (E)



## Available Packages

200 L Art. 81714

## Technical Data

Name	Value	Method
Colour	< 3,0	
Density at 15 °C	900 kg/m <sup>3</sup>	DIN EN ISO 12 185
Viscosity at 40 °C	220,0 mm <sup>2</sup> /s	ASTM D 7042
Viscosity index	> 90	ASTM D 2270
Flash Point (Cleveland)	>210 °C	ISO 2592
Pour Point	<-12 °C	ISO 3016
Corrosion protection towards steel	Corrosion degree 0	ISO 7120
Corrosion effect on copper	Corrosion degree 1	ISO 2160
Loading capacity according to Brugger	>50 N/mm <sup>2</sup>	DIN 51 347
FZG Test A/8,3/90	Damage loading step > 12	DIN 51 354/2

## Instructions

On refilling and changing the motor/gear oil please follow the operating instructions of the manufacturer.