

Benefits

1. optimal increase of engine service life
2. rapid oil supply even at low temperatures
3. suitable for engines with turbochargers

Product Description

BIZOL Allround 5W-40 is a fully synthetic, high-performance, low-friction engine oil designed for year-round use in modern engines. It reduces oil and fuel consumption and grants optimum lubrication even under extreme conditions. It ensures an immediate lubricating effect at cold start because of its constant wide-range viscosity, which resists even extreme temperature fluctuations. The unique compound of **BIZOL Allround 5W-40** ensures optimal engine performance and oil pressure at all speed ranges. The improved wear protection prolongs the service life of the engine.



Base Oil

Fully Synthetic

Specifications/Approvals & Recommendations

ACEA A3/B4 | API SN/CF

MB 229.5/229.3 | BMW LL 01 | VW 502 00/505 00 |

GM LL A-025/LL B-025 | Renault RN 0700/RN 0710 |

Fiat 9.55535 H2/9.55535 M2 | Porsche A40 | Peugeot B71 2296

Available Packages

1 L Art. 85010 4 L Art. 85016 5 L Art. 85011 20 L Art. 85012

60 L Art. 85013

Technical Data

| Name | Value | Method |
|---------------------|-------------------------|-------------|
| Viscosity class SAE | 5W-40 | |
| Viscosity at 40 °C | 82,2 mm ² /s | ASTM D 7042 |
| Viscosity at 100 °C | 14,3 mm ² /s | ASTM D 7042 |
| Viscosity index | 181 | ASTM D 2270 |

Technical Data

| Name | Value | Method |
|-------------------------|-----------------------|-------------------|
| Density at 15 °C | 848 kg/m ³ | DIN EN ISO 12 185 |
| Pour Point | -42 °C | ISO 3016 |
| Flash Point (Cleveland) | 220 °C | ISO 2592 |
| ASTM colour number | L3,0 | ASTM D1500 |
| Evaporation loss | 8,5 % | DIN 51 581 |
| Sulfate ashes | 1,00 % | DIN 51 575 |
| Total base number (TBN) | 10,0 mg KOH/g | ASTM D 2896 |

Instructions

On refilling and changing the Engine Oil please follow the operating instructions of the manufacturer.