

## Benefits

1. reduced CO2 emissions
2. improved fuel consumption
3. prolongs engine life

## Product Description

**BIZOL Moto 10W-40** is a low-viscosity oil based on HC synthesis technology. Its special application is in four-stroke engines in motorcycles and quads. It complies with the current JASO MA2 specifications and is specially formulated for use in motorcycle wet clutches. The reduction of deposits and prevention of sludging are guaranteed by the use of top-quality base oils and carefully-selected additives. **BIZOL Moto 10W-40** assures an outstanding protection from corrosion and the new-style formulation concept also saves fuel.



## Base Oil

HC-Synthetic

## Specifications/Approvals & Recommendations

API SL | JASO MA-2

## Available Packages

1 L Art. 18620

4 L Art. 18626

## Technical Data

Name	Value	Method
Viscosity class SAE	10W-40	
Viscosity at 40 °C	89,2 mm <sup>2</sup> /s	ASTM D 7042
Viscosity at 100 °C	13,9 mm <sup>2</sup> /s	ASTM D 7042
Viscosity index	157	ASTM D 2270
Density at 15 °C	860 kg/m <sup>3</sup>	DIN EN ISO 12 185
Pour Point	-39 °C	ISO 3016

## Technical Data

Name	Value	Method
ASTM colour number	L3,5	ASTM D1500
Flash Point (Cleveland)	225 °C	ISO 2592
Total base number (TBN)	8,0 mg KOH/g	ASTM D 2896