

Benefits

1. excellent wear protection
2. excellent thermal protection
3. excellent compatibility with wet clutches

Product Description

BIZOL Moto 20W-40 is a four-stroke engine oil for motorcycles and quads which meets the current JASO MA2 specification. The formulation ensures optimal wet clutch compatibility allowing precise and smooth gear changing. The advanced formulation keeps deposits at ultra-low levels and prevents the formation of sludge. A high alkaline reserve ensures good corrosion protection properties. Rounding off its profile is a new formulation concept that offers improved fuel economy and lower oil consumption.



Base Oil

Mineral

Specifications/Approvals & Recommendations

API SN | JASO MA-2

Available Packages

1 L Art. 18820

Technical Data

Name	Value	Method
Viscosity class SAE	20W-40	
Viscosity at 40 °C	89,7 mm ² /s	ASTM D 7042
Viscosity at 100 °C	14,1 mm ² /s	ASTM D 7042
Viscosity index	162	ASTM D 2270
Density at 15 °C	860 kg/m ³	DIN EN ISO 12 185
Pour Point	-39 °C	ISO 3016

Technical Data

Name	Value	Method
ASTM colour number	L3,5	ASTM D1500
Flash Point (Cleveland)	>220 °C	ISO 2592
Total base number (TBN)	8,0 mg KOH/g	ASTM D 2896

Instructions

On refilling and changing the Engine Oil please follow the operating instructions of the manufacturer.