

## Benefits

1. prolonged engine life
2. reduced oil consumption
3. improved fuel economy

## Product Description

**BIZOL Moto 10W-30** is a four-stroke engine oil for motorcycles and quads which meets the current JASO MA2 specification. The formulation ensures optimal wet clutch compatibility allowing precise and smooth gear changing. The advanced formulation keeps deposits at ultra-low levels and prevents the formation of sludge. A high alkaline reserve ensures good corrosion protection properties. Rounding off its profile is a new formulation concept that offers improved fuel economy and lower oil consumption.



## Base Oil

HC-Synthetic

## Specifications/Approvals & Recommendations

API SN | JASO MA-2

## Available Packages

1 L Art. 18720

## Technical Data

Name	Value	Method
Viscosity class SAE	10W-30	
Viscosity at 40 °C	69,8 mm <sup>2</sup> /s	ASTM D 7042
Viscosity at 100 °C	11,6 mm <sup>2</sup> /s	ASTM D 7042
Viscosity index	161	ASTM D 2270
Density at 15 °C	855 kg/m <sup>3</sup>	DIN EN ISO 12 185
Pour Point	-39 °C	ISO 3016

## Technical Data

Name	Value	Method
ASTM colour number	L3,5	ASTM D1500
Flash Point (Cleveland)	>200 °C	ISO 2592
Total base number (TBN)	10,0 mg KOH/g	ASTM D 2896

## Instructions

On refilling and changing the Engine Oil please follow the operating instructions of the manufacturer.